



**PT. GYUNG DO INDONESIA**

PAINT FOR WOOD, PLASTIC, METAL & FLOOR

---

## UNSATURATED POLYESTER PUTTY GPN – 0225 NATURAL / GPH – 006J

---

### Product Information

This product is 2 components unsaturated polyester putty based on polyester resin. It has good hardness, curing, sanding, pore or hole closing properties.

### Recommended Use

For wood

### Technical Data

<b>Appearance</b>	Viscous Milky Liquid
<b>Sp. Gr. (gr/cm<sup>3</sup>, 32°C)</b>	1.6~1.7 / 1.1~1.2 (Base/Catalyst)
<b>Drying Time (32°C)</b>	4~6 hrs.
<b>Application</b>	Scrapper
<b>Spray Viscosity (NK2,32°C)</b>	.....
<b>Theoretical Coverage (mix)</b>	.....
<b>Thinner</b>	GPT-040
<b>Gloss (60°)</b>	Matt
<b>Flash Point (°C )</b>	About 31
<b>Hardener</b>	GPH-006J
<b>Mixing ratio ( by wt )</b>	100 : 1 ( Base / Catalyst )
<b>Solid Content (%) (mix)</b>	80±1

### Surface Preparation

Remove oil, water, and dust.

### Precaution

1. After application, close the container tightly.