



PT. GYUNG DO INDONESIA

PAINT FOR WOOD, PLASTIC, METAL & FLOOR

ALKYD URETHANE SANDING SEALER HUS – 1900 CLEAR / HAD – 001CRP

Product Information

This product is 2 components urethane sanding sealer clear based on alkyd resin, polyisocyanate.

It has good hardness, drying, sanding properties.

Recommended Use

For wood

Technical Data

| | |
|--|---|
| Appearance | Viscous Milky Liquid |
| Sp. Gr. (gr/cm³, 32°C) | 1.0~1.1 / 0.9~1.0 (Base/Hardener) |
| Drying Time (32°C) | 1~2 hrs. |
| Application | Spray, Brush |
| Spray Viscosity (NK2,32°C) | 11~13 |
| Theoretical Coverage (mix) | 10 m ² /lt (DFT 50µm, WET 100) |
| Thinner | Urethane Thinner |
| Gloss (60°) | Semi gloss |
| Flash Point (°C) | About -4 |
| Hardener | HAD-001CRP |
| Mixing ratio (by wt) | 2 : 1 (Base / Hardener) |
| Solid Content (%) (mix) | 57±1 |

Surface Preparation

Remove oil, water, and dust.

Precaution

1. After application, close the container tightly.