



PT. GYUNG DO INDONESIA

PAINT FOR WOOD, PLASTIC, METAL & FLOOR

EPOXY ANTISTATIC SELF LEVELING GHDS – 9400 COLOR / GEH - 006

Product Information

This product is 2 components epoxy antistatic self leveling color based on epoxy resin, polyamine resin.

It has good curing, water and alkali resist, adhesion properties.

Its surface resistance is $10^5 \sim 10^7$ ohm / cm²

Recommended Use

For concret

Technical Data

Appearance	Viscous colored Liquid
Sp. Gr. (gr/cm³, 32°C)	1.4~1.5/0.9~1.0(Base/Hardener)
Drying Time (32°C)	12~16 hrs.
Application	Scraper, Brush, Roller
Spray Viscosity (NK2,32°C)	No thinning
Theoretical Coverage (mix)	1.3 kg / m ² (1mm)
Thinner	Epoxy Thinner
Gloss (60°)	Full gloss
Flash Point (°C)	About 65
Hardener	GEH-006
Mixing ratio (by wt)	3 : 1 (Base / Hardener)
Pot life (32°C)	30~40 min.
Solid Content (%) (mix)	99±1

Surface Preparation

Remove oil, water, and dust.

Precaution

1. After application, close the container tightly.