



**PT. GYUNG DO INDONESIA**  
PAINT FOR WOOD, PLASTIC, METAL & FLOOR

---

## STYRENE MODIFIED ALKYD ENAMEL COLOR GEP – 950 - 00

---

### Product Information

This product is 1 components styrene modified alkyd enamel color based on styrene modified alkyd resin.

It has good adhesion, fast drying.

### Recommended Use

For wood, steel

### Technical Data

<b>Appearance</b>	Viscous White Liquid
<b>Sp. Gr. (gr/cm<sup>3</sup>, 32°C)</b>	1.1 ~ 1.2
<b>Drying Time (32°C)</b>	4 ~ 5 hrs
<b>Application</b>	Spray, Brush, Roller
<b>Spray Viscosity (NK2,32°C)</b>	11~13
<b>Theoretical Coverage</b>	14 m <sup>2</sup> /lt (DFT 30µm, WET 70)
<b>Thinner</b>	Enamel Thinner
<b>Gloss (60°)</b>	Full Gloss
<b>Flash Point (°C )</b>	About 25
<b>Solid Content (%)</b>	58±1

### Surface Preparation

Remove oil, water, and dust.

### Precaution

1. After application, close the container tightly.
2. Mix enough for uniform paint.
3. Apply thin film thickness. Thick film can be wrinkled.