



**PT. GYUNG DO INDONESIA**  
PAINT FOR WOOD, PLASTIC, METAL & FLOOR

---

## EPOXY MASTIC COLOR

### GHDF – 3400 - 00 / GEH - 017

---

#### Product Information

This product is 2 components epoxy mastic color based on epoxy resin, polyamide resin. It has good curing, water and alkali resist, anticorrosive, high build, adhesion properties.

#### Recommended Use

For concret, steel

#### Technical Data

<b>Appearance</b>	Viscous White Liquid
<b>Sp. Gr. (gr/cm<sup>3</sup>, 32°C)</b>	1.6~1.7/0.9~1.0(Base/Hardener)
<b>Drying Time (32°C)</b>	8~10 hrs.
<b>Application</b>	Spray, Brush, Roller
<b>Spray Viscosity (NK2,32°C)</b>	11~13
<b>Theoretical Coverage (mix)</b>	6 m <sup>2</sup> /lt (DFT 100µm, WET 170µm)
<b>Thinner</b>	Epoxy Thinner
<b>Gloss (60°)</b>	Semi gloss
<b>Flash Point (°C )</b>	About 25
<b>Hardener</b>	GEH-017
<b>Mixing ratio ( by wt )</b>	4 : 1 ( Base / Hardener )
<b>Solid Content (%) (mix)</b>	75±1

#### Surface Preparation

Remove oil, water, and dust.

#### Precaution

1. After application, close the container tightly.