



**PT. GYUNG DO INDONESIA**

PAINT FOR WOOD, PLASTIC, METAL & FLOOR

---

## ALKYD URETHANE TOP COAT COLOR HUC – 1730-00 / HAD – 001QT

---

### Product Information

This product is 2 components urethane top coat color based on alkyd resin, polyisocyanate.

It has good hardness, drying.

### Recommended Use

For wood

### Technical Data

<b>Appearance</b>	Viscous White Liquid
<b>Sp. Gr. (gr/cm<sup>3</sup>, 32°C)</b>	1.2~1.3 / 0.9~1.0 (Base/Hardener)
<b>Drying Time (32°C)</b>	1~2 hrs.
<b>Application</b>	Spray, Brush
<b>Spray Viscosity (NK2,32°C)</b>	11~13
<b>Theoretical Coverage (mix)</b>	9 m <sup>2</sup> /lt (DFT 40µm, WET 100µm)
<b>Thinner</b>	Urethane Thinner
<b>Gloss (60°)</b>	Full gloss
<b>Flash Point (°C )</b>	About -4
<b>Hardener</b>	HAD-001QT
<b>Mixing ratio ( by wt )</b>	2 : 1 ( Base / Hardener )
<b>Solid Content (%) (mix)</b>	56±1

### Surface Preparation

Remove oil, water, and dust.

### Precaution

1. After application, close the container tightly.