



PT. GYUNG DO INDONESIA
PAINT FOR WOOD, PLASTIC, METAL & FLOOR

EPOXY ANTISTATIC TOP COAT COLOR GHDF – 9400 COLOR / GEH - 003

Product Information

This product is 2 components epoxy antistatic top coat color based on epoxy resin, polyamide resin.

It has good curing, water and alkali resist, adhesion properties.

Its surface resistance is $10^5 \sim 10^7 \Omega / \text{cm}^2$

Recommended Use

For concret

Technical Data

Appearance	Viscous Color Liquid
Sp. Gr. (gr/cm³, 32°C)	1.4~1.5/0.9~1.0(Base/Hardener)
Drying Time (32°C)	12~16 hrs.
Application	Spray, Brush, Roller
Spray Viscosity (NK2,32°C)	11~13
Theoretical Coverage (mix)	10 m ² /lt (DFT 50µm, WET 100)
Thinner	Epoxy Thinner
Gloss (60°)	Semi gloss
Flash Point (°C)	About 25
Hardener	GEH-003
Mixing ratio (by wt)	5 : 1 (Base / Hardener)
Solid Content (%) (mix)	71±1

Surface Preparation

Remove oil, water, and dust.

Precaution

1. After application, close the container tightly.